

TROJFÁZOVÉ PŘEPÍNATELNÉ MOTORY
THREE-PHASE MOTORS CHANGING
DREHSTROMMOTOREN POLUMS

Typ	s konstatním momentem	pro ventilátory	Hmotnost kg
	výkon W	výkon W	
1500/3000 min⁻¹			
TM71-4/2S	200/280	80/370	6,1
TM71-4/2M	250/370	100/500	7,0
TM71-4/2L	300/450	120/600	8,3
TM80-4/2S	450/600	150/750	8,2
TM80-4/2M	650/900	220/1100	9,4
TM80-4/2L	850/1320	270/1300	12,6
TM90-4/2S	1000/1400	300/1500	13,5
TM90-4/2L	1400/1700	400/2000	15,3
TM90-4/2X	1800/2300	480/2400	17,0
750/1500 min⁻¹			
TM71-8/4S	60/120	50/200	6,0
TM71-8/4M	90/200	70/300	7,0
TM71-8/4L	120/280	90/400	8,2
TM80-8/4S	200/400	120/500	8,2
TM80-8/4M	270/500	160/700	9,4
TM80-8/4L	300/650	220/900	12,6
TM90-8/4S	300/700	250/1000	13,5
TM90-8/4L	500/1000	350/1400	15,3
TM90-8/4X	700/1200	500/2000	17,0
1000/3000 min⁻¹			
TM71-6/2L		70/200	8,3
TM80-6/2M		120/370	9,4
TM80-6/2L		180/550	12,6
TM90-6/2S		300/1000	13,5
TM90-6/2S		500/1500	15,3
1000/1500 min⁻¹			
TM71-6/4S		60/180	6,1
TM71-6/4M	120/180	70/250	7,0
TM71-6/4L		90/300	8,3
TM80-6/4S	150/220	110/350	8,2
	200/350	180/550	9,4
	300/480	220/650	12,6
TM90-6/4S	370/550	240/750	13,5
TM90-6/4M	480/750	350/110	15,3
TM90-6/4X	600/900	500/1500	17,0
750/3000 min⁻¹			
TM71-8/2S		50/180	7,0
TM71-8/2M		90/300	8,3
TM80-8/2S		110/550	8,3
TM80-8/2M		150/750	9,4
TM90-8/2S		250/1000	13,5
TM90-8/2M		330/1350	15,3